

Clarke®

RS-16 Rotary Sander



www.americansanders.com

Clarke®
American Sanders

Because Pride Still Matters.

RS-16 Rotary Sander



KEY FEATURES

- Available in standard or dust control models
- Powerful 1.5HP motor provides smooth operation and aggressive sanding
- Innovative “wiper” style switch keeps the motor contacts clean
- Smooth and rugged steel planetary gear systems
- Chrome plated steel housing, motor cover, and handle tube provide maximum durability
- Grey non-marking wheels and power cord protect the floor
- Grip face pad driver supplied with the machine

SPECIFICATIONS

	RS-16	RS-16dc
Part Number	07161A	07162A
Pad Diameter	16"	
Pad Speed	175 RPM	
Voltage	120v/60hz	
Horsepower	1.5 hp (1.1 kW)	
Motor	Dual capacitor induction	
Gear Box	Triple planetary	
Power Cord	50', 14-3 non-marking grey	
Frame	Die cast aluminum alloy	
Wheels	5" (12.7 cm) non-marking grey	
Dust Skirt	NA	Reinforced nylon, quick removal
Dust Hose	NA	1.5" (36 mm)
Weight	91 lbs. (41.3 kg)	95 lbs. (43 kg)
Warranty	5 Years	



The RS-16dc can be easily attached to a vacuum to provide excellent dust control.



The wide stance of the transport wheels promote maximum stability when rolling over thresholds.



The simple modular switch design promotes fast and easy repairs to minimize maintenance.



Powerful 1.5 hp motor has dual capacitors to maximize startup and run torque.

Clarke®

2100 Hwy. 265
Springdale, AR 72764

www.americansanders.com

DISTRIBUTED BY:

Customer Relations: 1.800.253.0367
Fax Orders to: 1.800.825.2753
Technical Service: 1.800.356.7274